

切断长度<sub>(mm)</sub>

Cutting Length

激光切断: 自动寻的系统、采用大功率高效激光发生器, 切断 速度快,切断面平整、不发黄、不散丝。

光电感应器可准确定位商标,精确切在商标切断线上。 可切各种形状: 只要輸入长度、宽度、角度等参数,电脑将自动 切出你所需的如: 菱形、平行四边形、方形、宝塔形等各种形状。 送带机·自动送带,防缠绕解带。

障,系统将自动在屏幕上显示,方便维修。

自动暂停:一旦材料用完,系统将自动停止工作。 记忆功能:在开关关闭前,自动储存当前所设置的所有参数。

可切断材质

各种编织带魔术贴、鞋带、商标、各种带料等。

最大切断宽度(mm) 最大切断斜角(mm) 激光功率(w) 电压(v) 频率(Hz)

Max. Cutting Width Max. Cutting Angle Laser power Voltage



Frequency

50/60

Laser cutting: homing system with high power and high efficiency laser generator, fast cutting speed, the cutting surface is smooth, not yellow, not to

高精度:采用触摸屏操作系统,屏幕显示更直接,操作更方便。 High precision: the touch screen operating system, display a more direct, more convenient operation. Photoelectric sensor can accurately locate the trademark Convenient operation: Protocelectic sensor can accurately locate the trademark, accurate cutting line in the trademark.

Various shapes: as long as the input of length, width, angle and other parameters, the computer will automatically cut out you need such as: diamond,

这带机:自动这带、防缠绕解带。 故障自检:冷切机无水报警、无材料、色标传感器、一旦出现故 square, parallelogram, pagoda shape and other various shapes.
Belt feeding machine: automatic feed, with winding prevention function.

Self-check: cold cutting machine anhydrous alarm, no material, color code sensor, once faults occur, the system will automatically display on the screen, convenient repair. Automatic stopper: It stops automatically if materials run out during operation

Memory: Set-length, set-q'ty & set-speed are not erased even if power off & on.

Suitable for woven with Velcro. shoelaces. trademark, with various materials.

Weight

252

额定功率(w) 重 量 (kg)

SF-3800	20-99999	80	300	70	120	220			
	•			SF-21	100				
			超声波电脑切带机(大功率						
		The same		Ultrasonic Cuttir	ng Machine(po	wered)			
			74						

切断速度 (p/min)

超声波切断:采用进口大功率高效声波换能器,切断速度快, 切刀口不发黑、切断面平整、不散丝。不同材质无需换刀。 高精度:采用触摸屏操作系统,屏幕显示更直接,操作更方便。 每一次切断都由步进电机监控,以保证每次操作的高精确性。 切断宽度宽。采用独特的切刀平台,最宽可切 200mm。 自动操作・只要设定您所要的参数如・切断长度、数量等。其 余工作电脑自动完成。

故障自检: 切刀座、无材料、一旦出现故障,系统将自动在屏幕上

一旦材料用完,系统将自动停止工作。 自动暂停:

各种编织带、魔术贴、鞋带、拉链、码头装卸带、汽车安全带各种 皮质带料等



1000



包装尺寸L.W.H (mm)

Package Size

1626x1074x821

Ultrasonic Cutting: Balde is not black, ghost edge and feel comortable

Effcient: The powerful transducer cut faster, quiter. Touch screen: Large touch screen, the srceen display directly, easy

operation. Accurate: Cut-length is accurate owing to a stepping motor.

Cutting wide: Specail designe of workbench, cut with 200mm wide. Computerised: Automatic work, stop .The special fault selfdiagnosis, clear fualt zone

All kinds of Wovean Belts, Velcro, Shoelace, Zipper, Webbings, Safe Belts. And Kinds of Leather Belts. etc.

型 号	切断长度 <sub>(mm)</sub>	切断速度 (p/min)	最大切断宽度(mm)	声波频率 (Hz)	建议气压 (Mpa)	电压 (v)	额定功率(kw)	最大声波功率 (kw)	重 量 (kg)	机箱包装尺寸LW.H (mm)
Model	Cutting Length	Cutting Speed	Max. Cutting Width	Sound Frequency	Recommended Pressure	Voltage	Power	Power	Weight	Stand Package Size
SF-2100	15-99999	120	200	15K	0.4~0.7	220	1.5	3.5	178	760x690x1380



的刀模,如: 直角、圆角、燕尾等形状。

切刀口不发黑、切断面平整、不散丝。不同材质无需换刀。

光电感应器可准确定位商标,精确切在商标切断线上。

# 超声波切断:采用进口大功率高效声波换能器,切断速度快,

Ultrasonic cutting: Balde is not black, ghost edge and feel comortable. The powerful transducer cut faster, quiter. 高精度:采用触摸屏操作系统,屏幕显示更直接,操作更方便。 Accurate: The accurate cut of lables by using optronics sensor 切刀平台共享: 独特的切刀平台共享技术。可搭载多种形状

Storage: Memery all cuttings for your convenience.

转角功能: 只要输入长度、宽度、角度等参数, 电脑将自动切 出你所需的如:菱形、平行四边形、方形、宝塔形等各种形状。 故障自检:切刀座、无材料、色标传感器、转刀座一旦出现故 障,系统将自动在屏幕上显示,方便维修。

自动暂停:一日材料用完,系统将自动停止工作, 记忆功能: 在开关关闭前,自动储存当前所设置的所有参数。

### 可切断材质

各种编织带魔术贴、鞋带、拉链、商标、各种皮质带料等。



Varity shapes: The special technique of sharing flateform can carry variety shapes of knife molds and replace mold quickly.
Multi-angle: By use of multi-angle cut function of straight knife, can cut many shapes as parallelogram, rhombic, trapezoid, etc. Computerised: Automatic work and stop, the special fault self-diagnosis. Display directly the problems. Clear fault zone.

Suitable for Wovean Belts, Velcro, Shoelace, Zipper, Labels, And Kinds of Leather Belts. etc.

型 号	切断长度 <sub>(mm)</sub>	切断速度 (p/min)	最大切断宽度(mm)	最大切断斜度 (mm)	声波频率 (Hz)	建议气压 (Mpa)	电压 (v)	额定功率(kw)	最大声波功率 (kw)	重 量 (kg)	机箱包装尺寸LWH(mm)
Model	Cutting Length	Cutting Speed	Max. Cutting Width	Max. Cutting Angle	Sound Frequency	Recommended Pressure	Voltage	Power	Power	Weight	Stand Package Size
SF-2200	25-99999	120	100	45	20K	0.4~0.7	220	1.5	1.7	152	700x610x1450



SOFL®

高速: 每分钟可切断 80~100 片。(以 50mm 长度为例) 高精度:每一次切断都由步进电机监控,以保证每次操作的高精

切断面平整: 热刀可对彩色丝带、轻薄编织带的切断面进行热封, 且封口平整无毛边, 但对厚料效果不佳。刀刃由优质进口钢材制 成,使用寿命长。

自动操作: 只需设定您所需的切断长度和数量, 其余工作都自动 and quantity

自动暂停:一旦材料用完,将自动停止工作。 记忆功能: 在开关关闭前, 自动存储所设置的切断长度和切断数

量以及切断速度。

尼龙编织带、彩色缎带、背包带等尼龙材质。



High speed: It can cut 80~100 pcs per minute (50mm long) Accuracy: Cut-length is accurate owing to a stepping motor. Cutting type: Melting & cutting by hot knife, woven label is cut neatly without fraving

but not for heavy materials and installed with anti-static electricity device

Automatic operation: It works automatically only by setting length

Automatic stopper: It stops automatically if materials run out during operation

Memory: Set-length, set-g' ty & set-speed are not erased even if

Woven Tapes, Strip Tapes, Bag Band, etc. But no pure cotton

型 号	切断长度 <sub>(mm)</sub>	最大切断宽度 <sub>(mm)</sub>	切断速度 <sub>(p/min)</sub>	刀片最高温度(仓)	电压 (v)	频率 (Hz)	额定功率(kw)	包装尺寸L.W.H (mm)	重 量 (kg)	机箱包装尺寸L.W.H (mm)	重 量 (kg)	装箱率(台)
Model	Cutting Length	Max. Cutting Width	Cutting Speed	Max. Blade Temp	Voltage	Frequency	Power	Package Size	Weight	Stand Package Size	Weight	Loading Rate Pic
SF-130LR	1-99999	195	80-100	300	110/220	50/60	1.08	655x590x540	95/75	550x445x465	17	1



高速:每分钟可切断 80~100 片。(以 50mm 长度为例) 高精度:每一次切断都由步进电机监控,以保证每次操作的

切断面平整: 刀刃由优质进口钢材制成, 保证了切断面的 平整性。

自动操作:只需设定您所需的切断长度和数量,其余工作 都自动完成。

自动暂停:一旦材料用完,将自动停止工作。 记忆功能: 在开关关闭前,自动存储所设置的切断长度和

### 切断数量以及切断速度。 可切断材质

编织带、魔术贴、塑料软管、鞋带、塑料拉链、电脑排线。

High speed: It can cut 80~100 cut per minute. (50mm long) Accuracy: Cut-length is accurate owing to a stepping motor. Cutting type: Cutting is neat due to using a cold cutter which is durable because they are made of high-speed steel. Automatic operation: It works automatically only by setting length

and quantity. Automatic stopper: It stops automatically if materials run out during

Memory: Set-length, set-g'ty & set-speed are not erased even if

## power off & on.

Belt loop, soft tube, string, plastic zipper, elastic band, small

型 号	切断长度 <sub>(mm)</sub>	最大切断宽度 <sub>(mm)</sub>	切断速度 <sub>(p/min)</sub>	电压 (v)	频率 (Hz)	额定功率(kw)	包装尺寸L.W.H (mm)	重 量 (kg)	机箱包装尺寸L.W.H (mm)	重 量 (kg)	装箱率(台)
Model	Cutting Length	Max. Cutting Width	Cutting Speed	Voltage	Frequency	Power	Package Size	Weight	Stand	Weight	Loading Rate Pic
SF-130L	1-99999	200	80-100	110/220	50/60	0.5	655x590x540	95/75	550x445x465	17	1







高速:每分钟可切断 80~00 片。(以 50mm 长度为例) 高精度:每一次切断都由步进电机监控,以保证每次操作的高精

切断面平整: 热刀可对彩色丝带、轻薄编织带的切断面进行热封, 且封口平整无毛边,但对厚料效果不佳。刀刃由优质进口钢材制 anti-static electricity device. 成,使用寿命长。

自动操作: 只需设定您所需的切断长度和数量, 其余工作都自动 and quantity.

自动暂停:一旦材料用完,将自动停止工作。 记忆功能: 在开关关闭前, 自动存储所设置的切断长度和切断数

### 量以及切断速度。 可切断材质

编织带、尼龙织带、彩色缎带、背包带等尼龙材质。

### Special features

High speed: It can cut 80~100 pcs per minute. (50mm long) Accuracy: Cut-length is accurate owing to a stepping motor. Cutting type: Melting & cutting by hot knife, woven label is cut neatly without fraying but not for heavy materials and installed with

Automatic operation: It works automatically only by setting length

Automatic stopper: It stops automatically if materials run out during

operation. Memory: Set-length, set-q' ty & set-speed are not erased even if

# power off & on.

Belt loop, bag band, shrink tube, string, elastic band, plastic

型 号	切断长度 <sub>(mm)</sub>	最大切断宽度 <sub>(mm)</sub>	切断速度 <sub>(p/min)</sub>	刀片最高温度(%)	电压 (v)	频率 (Hz)	额定功率(kw)	包装尺寸L.W.H (mm)	重 量 (kg)	装箱率(台)
Model	Cutting Length	Max. Cutting Width	Cutting Speed	Max. Blade Temp	Voltage	Frequency	Power	Package Size	Weight	Loading Rate Pic
SF-120LR	1-99999	95	90	250	110/220	50/60	0.66	410x525x430	24/29	1