





可切断材质

塑料软管、鞋带、塑料拉链、电脑排线。

活用干鞋、帽、箱包,是服装生产、线带加工、电器装配等行业的 配套设备。可任意调节送料长度,具备自动进料计数功能,工效 高、嗓音低、体积小、重量轻、操作方便等特点。 weight, easy to operate and so on.

Woven tapes, soft tube, string, plastic zipper, small webbing, etc.

型 号	切断长度 _(mm)	最大切断宽度 _(mm)	切断速度 _(p/min)	包装尺寸L.W.H (mm)	重 量 _(kg)	装箱率(台)
Model	Cutting Length	Max. Cutting Width	Cutting Speed	Package Size	Weight	Loading Rate Pic
SF-812	15-100	50	80-90	400x275x285	16	1





适用于鞋、帽、箱包,是服装生产、线带加工、电器装配等行业的配套设备。可任意调节送料长度,具备自动进料计数功能,工效量。 服务保 体和 医唇头 操作工 原管体上 高、噪音低、体积小、重量轻、操作方便等特点。

编织带、魔术贴、塑料软管、鞋带、塑料拉链、电脑排线。

automatic feed, higher efficiency, low noise, small size and light weight easy to operate and so on

Woven tapes, soft tube, string, plastic zipper, small webbing, etc.

型 号	切断长度 _(mm)	最大切断宽度 _(mm)	切断速度 _(p/min)	包装尺寸L.W.H (mm)	重 量 _(kg)	装箱率(台)
Model	Cutting Length	Max. Cutting Width	Cutting Speed	Package Size	Weight	Loading Rate Pic
SF-815	15-1500	50	23-35	500x340x455	23	1



切带机(冷、热刀)





功能特性 适用于鞋、帽、箱包,是服装生产、线带加工、电器装配等行业的 It is a mechineal tape cutting machine. for clothing production lines 配套设备。可任意调节送料长度,具备自动进料计数功能,热力 With soft matericals, electrical equipment assembly industries. Feeding length can be freely adjusted, it has the counting function 可对彩色丝带、轻薄编织带的切断面进行热封, 且封口平整无 毛边,但对厚料效果不佳。具有工效高、噪音低、体积小、重量 轻、操作方便等特点。

可切断材质

编织带、尼龙织带、彩色缎带、背包带、等尼龙带料。

with automatic feed, automatically heat-sealing for nylon materials,

woven label is cut neatly without fraying but not for heavy materials higher efficiency, low noise, small size and light weight, easy to operate, and so on.

It is specially designed for round velcro tape that need cetfillet. Feeding length can be freely adjusted, it has the length of the

small size and light weight, easy to operate.

counting function with automatic feed, higher efficiency, low noise

Woven tapes, ribbon tape, bag band, etc.

型 号	切断长度 _(mm)	最大切断宽度 _(mm)	切断速度 _(p/min)	刀片最高温度(飞)	包装尺寸L.W.H (mm)	重 量 _(kg)	装箱率(台)
Model	Cutting Length	Max. Cutting Width	Cutting Speed	Max. Blade Temp	Package Size	Weight	Loading Rate Pic
SF-817	15-1500	60	23-35	320	500x340x455	23	1



切带机(圆角

Apllication

Velcro tapes



可切断圆角、椭圆、整圆等形状。是服装生产、线带加工、电器装

可任意调节送料长度, 具备自动进料计数功能, 工效高、噪音 低、体积小、重量轻、操作方便等特点。

可切断材质

磨术贴。

型 号	切断长度 _(mm)	最大切断宽度 _(mm)	切断速度 _(p/min)	包装尺寸L.W.H (mm)	重 量 _(kg)	装箱率(台)
Model	Cutting Length	Max. Cutting Width	Cutting Speed	Package Size	Weight	Loading Rate Pic
SF-818	15-1500	50	23-35	500x340x455	23	1



automatic Button Feeder

Direct Drive Button Sewing Machine/

实现最高 2,700sti/min 的高速化,采用高速切线从而进一步提高了生产

通过独特的水平强制送扣机构确保送扣夹能地向钮夹送扣,无需熟练的 操作者。此外,操作者只需将面料放到指定位置,踩下脚踏板即可,减轻 了疲劳度。

」被另成。 操作面板:多种功能通过操作控制面板上的旋钮就能简单地进行设定。 此外,相应故障的报警灯闪动,即可快速地进行故障处理。







Fo realize high speed up to 2700sti/min, using high speed tangent

to further improve production efficiency. Sing ringin speed unique to further improve production efficiency. Through the unique levels forced buckle mechanism to ensure that the clip can send to pinch button button, without the need for skilled operator. In addition, an operator only needs the fabric into

he specified location, step on the foot pedal, reduce fatigue.

Operation panel: a variety of functions simply by operating the control knob can be set on the panel. In addition, the corresponding fault alarm lights flashing, can quickly make

型 号	机针	纽扣直径(mm)	缝制针距长度(mm)	压脚高度 _(mm)	标准花样数	可存储数	储存媒介	送扣模式	转速(r/min)	体积 _(V)	重 量 (kg)
Model	Needle	Button Diameter	Stitch length	Height of Presser Foot	Standard pattern number	Can store number	Storage media	Send button mode	Speed	Packing Size	Weight
SF-378-1903	PTX17	#14 8~32	0.1~10	最大13	50花样	200花样 可追加150花样	EEP-ROM EP-ROM	自动送扣模式、 单独模式、小批量模式	2700	1000x765x570	135



自动送扣机

Automatic Button Feeding Sewing Machine

多种机型配套:可搭配目前所有品牌型号钉扣机,安装方便,无需更

调节方便:不同尺寸的纽扣能方便的调节、纽扣的厚蓮可自动调节。 定位更准确: 采用高效的电脑、步进电机、伺服电机控制,工作更稳定、 定位更准确。

故障自检: 具有相应故障功能报警系统,可快速进行故障排除。 计数系统: 具有计数系统,可统计工作量,提高工作效率。 使用方便·无雲孰练的操作者也可以快速学会并使用。

Special reactives.

A variety of models supporting: easy installation on all kinds of button sewing machine without changing sewing table.

Convenient: auto sizing chute with thickness free, regardless of the button size

Correlate. Lauto Sarrig Value Will Manufaes Hee; pagalutess of the Dullon See Accurate positioning: the efficient use of the computer, stepping motor, servo motor control, more stable, more accurate positioning. Fault self diagnosis function: with the corresponding faultalarm system, rapid

troubleshooting. Counting system: with counting system, statistical work, improve work efficiency Easy to use: no need of skilled operator also can quickly learn and use

型 号	规格	纽扣直径 (mm)	纽扣厚薄 (mm)	功率 (w)	电压 _(V)	重量 (kg)	体积 (v)
Model	Button	Diamm	thickness	Power	Voltage	Weight	Packing Size
SF-378	27L/47L	8~30	1.5~7	0.45	220	78	820x620x570



单针之字缝锁式线迹钉扣机

Button Sewing Machine

标准型号备有普通之字及四针之字缝线迹;

之字缝)以降低机针偏差:





之字缝机械结构采用双偏心凸轮(普通之字缝)和新款式凸轮(四针 该两项功能提供最佳的之字缝缝纫效果,更能大大增加缝纫机的耐用

The standard model has the common characters and four zigzag stitching needle; Zigzag structure adopts double eccentric cam (common zigzag)

and the new type cam (four needle zigzag) to reduce the machine needle deviation;

The two functions provide the best zigzag sewing effect, can greatly increase the durability and reliability of sewing machine.

型 号	机 针	纽扣直径(mm)	自动剪线	压脚高度(mm)	钉缝针数	L)M)	转速(r/min)	电压 (v)	体积 _(V)	重 量 (kg)
Model	Needle	Button Diameter	Auto Matic Trim	Height of Presser Foot	Stitch No.		Speed	Voltage	Packing Size	Weight
SF-917	TQX1 #16	10~20	X(2.0~6.5) Y(0~6.5)	14	8,16,32	<u>L</u> M	0-1500	220	580x465x430	26.5/29.5











切能符性			
快速适应多种缝制要求,	对应缝制的变化	可通过简单的	内操作讲经
刃列り刃钉扣形式的变	更。也可以通过简单	1 握纵 杆转换	"-" 5 "X"

作方便、省电、高效率、低噪音、寿命长。

4	This machine is able to over the stitching mode between 2 noi
喿	and 4 holed buttons according to any design change. In addition
	stitchshape can be easily changed over between "="and "X". ea
	operation, low electric comsuption, high efficency, low noise, lo
	life-time.

	_									
型 号	机针	纽扣直径(mm)	自动剪线	压脚高度 _(mm)	钉缝针数	000	转速(r/min)	电压(v)	体积 _(V)	重 量 (kg)
Model	Needle	Button Diameter	Auto Matic Trim	Height of Presser Foot	Stitch No.	(F)(W)	Speed	Voltage	Packing Size	Weight
SF-2377D	14#~18# TQX1 #16	10~28	X(2.5~6.5) Y(0,2.5~6.5)	>9	8,16,32,6,12,24	<u>L</u> M	0-1500	220	580x465x430	26.5/29.5